COMMERCIAL



Traffic and weather conditions are not a problem anymore.
Thanks to the high standards of durability and maneuverability every product in this range is the solution for any daily routine.

Power Trailer



NON DIRECTIONAL

JA/KA-108

CITY | WEAR LIFE | DURABILITY | S2WR2 READY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
125R12C	81/79N		3,5	510	127	5,5	462	1019	437	963	5,25	76
145/70R12C	86N		4,0	506	138	5,1	530	1168	-	-	4,25	65
155/70R12C	104N/102N		4,5	523	155	5,8	900	1980	850	1870	6,5	94
185/60R12C	104N/102N		5,5	527	185	6,2	900	1980	850	1870	6,5	94
195/60R12C	104N/102N		6,0	531	194	7,4	900	1980	850	1870	6,5	94
195/50R13C	104N/102N		6,0	525	191	7,6	900	1980	850	1870	6,5	94



Power Trouper

NON DIRECTIONAL

KR-106

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
195R15C	103/101R	6	5,5	694	200	8,2	875	1930	825	1820	3,75	55
195R15C	106/104R	8	5,5	694	200	8,2	950	2095	900	1985	4,5	65



Power Trekker

NON DIRECTIONAL

KA-105

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
6.50R14C	102/100P	8	5,0	696	187	9,8	850	1875	800	1765	4,5	65
195R14C	106/104P	8	5,5	679	204	9,2	950	2095	900	1985	4,5	65
195/85R15LT	113/111L	-	5,5	710	195	8,6	1150	2535	1090	2405	6,0	87
215/70R15C	109/107R	8	6,5	683	220	10,2	1030	2270	975	2150	4,5	65
225/70R15C	112/110R	8	6,5	698	228	10,2	1120	2470	1060	2335	4,5	65
195/85R16LT	114/112L	-	5,5	737	193	8,6	1180	2600	1120	2470	6,0	87
215/70R16C	108/106T	6	6,5	708	221	10,0	1000	2205	950	2095	3,75	55



Power Cruiser

NON DIRECTIONAL

KA-104

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
6.50R14C	102/100P	8	5,0	696	187	9,8	850	1875	800	1765	4,5	65



Power Ranger

NON DIRECTIONAL

KA-103

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
195R14C	106/104N	8	5,5	668	200	9,9	950	2095	900	1985	4,5	65
215/70R15C	109/107R	8	6,5	683	220	10,2	1030	2270	975	2150	4,5	65
225/70R15C	112/110R	8	6,5	698	228	10,2	1120	2470	1060	2335	4,5	65
215/65R16C	106/104S	8	6,5	686	218	10,0	950	2094	900	1984	3,75	55



Power Saver II

NON DIRECTIONAL

KA-102

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
195R15C	103/101R	6	5,5	689	197	8,2	875	1930	825	1820	3,75	55
195R15C	106/104R	8	5,5	689	197	8,2	950	2095	900	1985	4,5	65



Power Saver

NON DIRECTIONAL

KA-101

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
165R13C	94/92N	8	4,5	601	165	9,0	670	1475	640	1410	4,5	65
175R13C	97/95N	8	5,0	613	177	9,5	730	1610	690	1520	4,5	65
185R14C	104/102N	8	5,5	653	190	10,3	900	1985	850	1875	4,5	65



Super Power

NON DIRECTIONAL

JR-101

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
5.00R12LT	77/75P	6	3,5	564	137	9,3	415	915	395	870	3,75	55
5.00R12LT	83/81P	8	3,5	564	143	9,3	485	1070	465	1025	4,5	65



Super Power

NON DIRECTIONAL

JR/KR-102

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
155R12C	88/86P	8	4,5	556	158	8,5	560	1235	530	1170	4,5	65
5.00R12LT	83/81P	8	3,5	567	148	9,5	485	1070	465	1025	4,5	65
5.50R12LT	92/90P	10	4,0	598	166	8,7	630	1389	600	1323	5,0	73
5.50R12LT	96/94P	12	4,0	598	166	8,7	710	1565	670	1477	6,0	87
5.50R13LT	95/93P	10	4,0	628	166	8,9	690	1520	655	1445	5,25	76
5.50R13LT	99/97P	12	4,0	628	166	8,9	765	1690	725	1600	6,25	91
5.50R13LT	102/100P	14	4,0	628	166	8,9	850	1874	800	1764	7,25	105



NON DIRECTIONAL

KR-355

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
195R15C	106/104R	8	5,5	694	195	9,0	950	2094	900	1984	4,5	65



NON DIRECTIONAL

KR-356

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.50R16LT	122/121L	14	5,5	808	209	11,6	1510	3330	1440	3175	7,0	102



Steel Techno

NON DIRECTIONAL

KR-302

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.00R16LT	113/111N	10	5,5	773	193	9,8	1130	2490	1075	2370	5,25	76
7.00R16LT	115/114N	12	5,5	773	198	9,8	1230	2710	1170	2580	6,0	87
7.00R16LT	118/116N	14	5,5	773	198	9,8	1320	2905	1260	2775	6,5	94
7.50R16LT	121/119N	12	5,5	800	210	10,2	1440	3175	1370	3020	6,5	94
7.50R16LT	122/121L	14	5,5	800	210	10,2	1510	3330	1440	3175	7,0	102



Steel Techno

NON DIRECTIONAL

KR-304

CITY | WEAR LIFE | DURABILITY

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.50R16LT All Steel	122/121L	14	5,5	810	209	11,6	1510	3330	1440	3175	7,0	102



Steel Force

NON DIRECTIONAL

KA/ZA-305A

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.50R16LT	122/121L	14	5,5	810	210	12,8	1510	3330	1440	3175	7,0	102
8.25R16LT	126/125L	14	6,5	860	234	14,5	1710	3770	1630	3595	6,25	91



Power Razor

NON DIRECTIONAL

KR-352

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
235/50R14LT	102L	-	7,5	598	231	8,4	850	1875	-	-	4,5	65



NON DIRECTIONAL

KA/ZA-353

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.50R16LT	122/121F	14	5,5	812	205	15,1	1510	3330	1440	3175	7,0	102



NON DIRECTIONAL

KA-354

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
7.50R16LT	114/112N	8	5,5	808	203	12,0	1175	2590	1120	2469	4,75	69



Evotrac DT

NON DIRECTIONAL

KR-112

CITY | OFF-ROAD | WEAR LIFE | LOW NOISE | SAVE FUEL

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
225/95R16C	118/116R	8	6,0	831	215	7,5	1320	2910	1250	2756	4,75	69



Super Cargo

NON DIRECTIONAL

KU-261

CITY | WEAR LIFE | DURABILITY | RAIN & WET

SIZE	LI/SI index	P.R.	R.W. inch	O.D. mm	S.W. mm	N.S.D. mm	MAX LOAD				INFLATION	
							SINGLE		DOUBLE		bar	psi
							kg	lbs.	kg	lbs.		
5.00R12LT	88/86P	10	3,5	568	142	9,5	560	1235	530	1170	5,5	80